

# Banked Fryer

## Model EOF-20/FFLT/24 or EOF-20/FFLT/24/24



Model: EOF-20/FFLT/24



Model: EOF-20/FFLT/24/24

**Now you're Cooking!** You can take increased productivity and take profits to the "Bank" with the Giles Banked Fryer. The Giles Banked Fryer is designed for foodservice operations where getting large quantities of product cooked quickly is important. In the standard configuration (one 20-inch and one 24-inch unit) the Giles Banked Fryer can produce tremendous amounts of fried products. With additional components, your Giles Banked Fryer can produce even more product.


The Giles Banked Fryer cooks food quickly and with our fast recovery times, you won't waste time waiting for oil that has lost its temperature. This revolutionary cooking system offers fast and delicious product.

The Giles Banked Fryer is simple to use. The durable, accurate timing system is engineered to be user friendly. All controls for the built-in filtering system are located in a central section of the fryer to minimize workload and make filtering easy. There is also available a "Zero Space" model which has no landing table.

The Giles Autolift System is standard on the 20-inch fryer and optional on the 24-inch fryer. Other options include a melt cycle for Canadian units and customization of the type of cooking compartments with up to three 24-inch units combined into a single Giles Banked Fryer.

For more information on the Giles Banked Fryer or any of our other foodservice products call 1-800-554-4537 (in the US or Canada) or 1-334-272-1457.

### Design Features



#### Automatic Basket Lift

The Automatic Basket Lift enables the operator to load the fryer, set the timer and activate the basket lift in one step. When the frying cycle is complete, the basket is automatically raised out of the shortening, allowing for safe and easy unloading of the product.



#### Automatic Oil Filtration System

Designed to complete a filter cycle within five minutes, the Automatic Oil Filtration System, which uses disposable filter paper, allows the operator to wash, rinse, drain, and filter the oil in one motion. Refilling the Fry Vat is automatic. The system will increase your shortening life by 50%.

### Listings



**Giles Foodservice Equipment** A Division of Giles Enterprises, Inc.

An ISO 9001 Registered Company

P.O. Box 210247 • 2750 Gunter Park Drive West • Montgomery, AL 36121-0247 USA


334.272.1457 • Fax 334.272.3561 • Phone Toll Free 1.800.554.4537

Web Site: [www.gilesent.com](http://www.gilesent.com) • Email: [info@gilesent.com](mailto:info@gilesent.com)

# Banked Fryer

## Model EOF-20/FFLT/24 or EOF-20/FFLT/24/24

Item No.: \_\_\_\_\_  
 Quantity: \_\_\_\_\_  
 Project Name: \_\_\_\_\_  
 SIS#: \_\_\_\_\_  
 AIA/CSI#: \_\_\_\_\_



Inches [millimeters]

Front

Side

### Specifications

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements additions or replacements or previously purchased equipment.

#### Construction:

Cabinet and Fry Vat: 20Ga to 16Ga Stainless Steel  
 Heating Element: Stainless Steel Round

#### Cooking Computer (1) per vat:

- (1) Adjustable Cooking Temperature, Max. Temperature: 375°F [190°C]
- (2) Timer Cycles, each cycle with (4) presets
- High Limit Thermostat: 450°F [220°C]

#### Capacity:

- 20" Vat: Shortening Capacity: 115 lbs. [52 kg]  
 Production Capacity: 27-30 lbs [12-14 kg] of cut chicken (80 pieces) using 3-1/2 lb [1.5 kg] bird.
- 24" Vat: Shortening Capacity: 170 lbs. [77 kg]  
 Production Capacity: 36-42 lbs [16-19 kg] of cut chicken (96 pieces) using 3-1/2 lb [1.5 kg] bird.

#### Electrical Specifications:

Available voltages: 208/240/480V -20" Vat -24,000 WATTS  
 -24" Vat -30,000 WATTS

- 20" Vat -3 phase - 208/240/480V - 76/66/33 AMPS
  - 20" Vat -1 phase - 208/240V - 115/100 AMPS
  - 24" Vat -3 phase - 208/240/480V - 100/87/43 AMPS
  - 24" Vat -1 phase - 208/240V - 144/125 AMPS
- (No service cord provided)

#### Listings:

UL (US and Canada), UL Sanitation, CE

#### Shipping Specifications:

Crated Weight: 1069 lbs [485 kg] EOF-20/FFLT/24  
 Crated Weight: 1311 lbs [595 kg] EOF-20/FFLT/24/24  
 Crated Cube Size: 50" D X 108" L X 61" H = 190.6 cu ft  
 [1270mm X 2743mm X 1549mm = 5.4 cu meters]

### Accessories Included

Unit is shipped with (4) Fry baskets -if EOF-20/FFLT/24 (Product Scoop may be substituted for (2) Baskets), (6) Fry baskets -if EOF-20/FFLT/24/24 (Product Scoop may be substituted for (2) Baskets), (2) Fry Screens, (1) FFLT Drain screen, (1) Drain hose wand, (5) Filter paper sheets, (1) Pot brush, (1) Kettle drain brush, (1) Stir paddle, (1) Crumb shovel, (1) Vat drain clean out and (1) Manual.

### How To Specify

#### 1. Model and Electrical Options

Specify the part number from the following:

	Voltage	Hz	Phase	Model	Part Number
<input type="checkbox"/>	208	60	1	EOF-20/FFLT/24	70957
<input type="checkbox"/>	208	60	3	EOF-20/FFLT/24	70959
<input type="checkbox"/>	240	60	1	EOF-20/FFLT/24	70958
<input type="checkbox"/>	240	60	3	EOF-20/FFLT/24	70960
<input type="checkbox"/>	480	60	3	EOF-20/FFLT/24	70961
<input type="checkbox"/>	208	60	1	EOF-20/FFLT/24/24	70962
<input type="checkbox"/>	208	60	3	EOF-20/FFLT/24/24	70964
<input type="checkbox"/>	240	60	1	EOF-20/FFLT/24/24	70963
<input type="checkbox"/>	240	60	3	EOF-20/FFLT/24/24	70965
<input type="checkbox"/>	480	60	3	EOF-20/FFLT/24/24	70966

#### 2. Accessories\*

Specify the part number and quantity of the following accessory items needed:

	Qty	Description	Part Number
<input type="checkbox"/>		Product Scoop	70430
<input type="checkbox"/>		Basket, EOF-20	70420
<input type="checkbox"/>		Basket, EOF-24	70421
<input type="checkbox"/>		Screen, FFLT	70085
<input type="checkbox"/>		Filter Paper, (100) Sheets	65491
<input type="checkbox"/>		Filter Powder, (60) packets	72004
<input type="checkbox"/>		Boil Out (4) 8 lb containers	72003

\*Additional charges

#### 3. Shipping

Specify the shipping method

### Giles Foodservice Equipment

P.O. Box 210247 • 2750 Gunter Park Drive West • Montgomery, AL 36121-0247 USA  
 334.272.1457 • Fax 334.272.3561 • Phone Toll Free 1.800.554.4537  
 Web Site: www.gilesent.com • Email: info@gilesent.com